

# PALLINA

Datasheet



The PALLINA is specially developed for Triodos Bank located at Estate "De Reehorst". This robust but efficient pathlighting is perfect for a wide light distribution on walking trails. The bollard has two led modules that are mounted in a perfect angle.



**timberlab**  
natural outdoor solutions



## SPECIFICATIONS

- **Dimensions:** 150mm
- **IP grade:** IP54
- **Power per LED module:** 2.4 Watt
- **Lumen output per LED module:**

2.700K = 133 lm
4.000K = 172 lm
amber = 60 lm
- **Beam angle:** 155x65\*
- **Lifespan:** Every type of wood has its own durability class. More information can be found at "Wood species" & "Sustainability". The LED module has an expected lifespan of 108.000 hours.
- **Photometric data:** Available on request.




## OPTIONS

- **Wood species:** Oak, chestnut or Accoya
- **Voltage:** 230 VAC or 12-24 V AC/DC
- **Certification:** FSC or PEFC
- **Colour temperature:** Available in 2.700K, 4.000K and Amber (593nm).
- **Cable:** Available with 0,6mtr 3x 1,5mm<sup>2</sup> cable or a 32mm hole for an easy connection to your ground cable.
- **Variations :** All Timberlab products are unique. In addition to our standard options, we offer customization. Think of adding logos, sockets or different dimensions.




Only products indicated with the FSC® claim are FSC certified and come with our FSC-certificate number NC-COC-029615-KE. Only products indicated with the PEFC™ claim are 100% PEFC certified and come with our PEFC-certificate number NC-PEFC/COC-029615-FJ.

LED MODULES

			
Voltage (optional)	230 VAC 12-24VAC/DC	230 VAC 12-24VAC/DC	230 VAC 12-24VAC/DC
Power	2.4W*	2.4W*	2.1W*
Power factor	0.36*	0.36*	0.34*
Lumen output	133 lm*	172 lm*	60 lm*
Efficiency	56 lm/W*	70 lm/W*	28 lm/W*
Colour temp.	Warm White 2700K 2625K*	Cool White 4000K 3812K*	AMBER x=0.5935 y=0.4043*
CRI	83*	71*	n.a.
Dimmable	on request	on request	on request
Label	A+	A++	A
IP grade	IP 54	IP 54	IP 54
Beam angle	95x22*	94x22*	79x17*
Number of LEDs	1	1	1
Temperature range in operation	-20...+50°C	-20...+50°C	-20...+50°C
Lifespan	100.000 h	100.000 h	100.000 h
* Measured values			

DIMENSIONS AND WEIGHT



L = Length

Weight chestnut	8 kg
Weight oak	10 kg
Weight Accoya	7 kg

CO2 storage chestnut	12 kg
CO2 storage oak	15 kg
CO2 storage Accoya	11 kg

PRODUCT CODE GENERATOR

Product family	Wood species	Certification	In ground / post support	Colour temp.	Type	Voltage	Variations
XX	X	X	XX	X	X	X	XX
26= PALLINA	2= Chestnut 3= Oak 4= Accoya	0= N.a. 1= FSC 2= PEFC	00 = Length 1 + 600mm in ground	1= 2.700K 3= 4.000K 4= Amber	0= 32mm hole 1= Cable	1= 230 V 2= 12-24V	00

EXAMPLE

PALLINA, Oak, PEFC, Length 1 + 600mm in ground, 2.700K, 32mm hole, 230V

Product code: 26320010100